

Claims

1. – 66. (canceled)

67. (currently amended) A computer-implemented method of decoding video with a video decoder, the method comprising:

at the video decoder, receiving multiple sets of reference decoder parameters signaled for a given bit stream of encoded data for a given video clip, wherein each of the multiple sets comprises a rate parameter and a decoder buffer size parameter for a reference decoder model that specifies constraints on fluctuations of the given bit stream of encoded data for the given video clip, and wherein each of the multiple sets indicates a different and alternative combination of rate parameter and decoder buffer size parameter for the same video images in the given bit stream of encoded data for the given video clip;

with the video decoder, determining an operating condition using any of the multiple sets, wherein the operating condition indicates peak rate or decoder buffer size for decoding the encoded data for the given video clip, and wherein the multiple sets are concurrently available for use in the determining the operating condition; and

~~at a decoder with the video decoder, receiving and~~ decoding the encoded data for the given video clip in accordance with the operating condition.

68. (previously presented) The method of claim 67 wherein the decoder buffer size parameter for each of the multiple sets is different.

69. (previously presented) The method of claim 67 wherein the rate parameter for each of the multiple sets is different.

70. (canceled)

71. (currently amended) The method of claim 67 further comprising:

at the video decoder, receiving multiple additional sets of reference decoder parameters;
with the video decoder, re-determining the operating condition using any of the multiple

additional sets; and

~~at the decoder with the video decoder, receiving and~~ decoding the encoded data for the given video clip in accordance with the re-determined operating condition.

72. (currently amended) The method of claim 67 further comprising, at the video decoder, receiving a number parameter that indicates how many sets of reference decoder parameters are signaled for the given bit stream of encoded data for the given video clip.

73. (previously presented) The method of claim 67 wherein the determining comprises selecting a parameter of one of the multiple sets.

74. (previously presented) The method of claim 67 wherein the determining comprises interpolating between parameters of two of the multiple sets.

75. (previously presented) The method of claim 67 wherein the determining comprises extrapolating from a parameter of one of the multiple sets.

76. (previously presented) The method of claim 67 wherein the peak rate is minimum peak rate, and wherein the determining comprises setting the minimum peak rate based upon one or more of the decoder buffer size parameters of the multiple sets.

77. (previously presented) The method of claim 67 wherein the determining comprises setting the decoder buffer size based upon one or more of the rate parameters of the multiple sets.

78. (previously presented) The method of claim 67 wherein the multiple sets are signaled in a stream header for the given bit stream of encoded data for the given video clip.

79. (previously presented) The method of claim 67 wherein the multiple sets are signaled out-of-band for the given video clip.

80. (previously presented) The method of claim 67 wherein each of the multiple sets further comprises an initial buffer fullness parameter.

81. (previously presented) The method of claim 67 wherein each of the multiple sets represents a different leaky bucket model for the given bit stream of encoded data for the given video clip.

82. (previously presented) The method of claim 67 wherein each of the multiple sets represents a different point along a rate-decoder buffer size curve for the given bit stream of encoded data for the given video clip.

83. (previously presented) The method of claim 67 wherein the given video clip is an entire video sequence.

84. (previously presented) The method of claim 67 wherein the given video clip is part of a video sequence.

85. (previously presented) The method of claim 67 wherein the decoder is implemented in a handheld computing device.

86. (previously presented) The method of claim 67 wherein the decoder is implemented in a personal computer.

87. (previously presented) The method of claim 67 wherein the decoder is implemented in a disk media player.

88. (previously presented) The method of claim 67 wherein the peak rate corresponds to a drive speed for a disk drive during the decoding the encoded data.

89. (previously presented) The method of claim 67 wherein the peak rate corresponds to a

transmission rate for a network connection during the decoding the encoded data.

90. (previously presented) The method of claim 67 wherein the decoding the encoded data occurs during live video transmission for the given video clip.

91. (previously presented) The method of claim 67 wherein the decoding the encoded data occurs during on-demand transmission for the given video clip.

92. (currently amended) A computer-implemented method of decoding video with a video decoder, the method comprising:

at the video decoder, receiving multiple sets of reference decoder parameters signaled for a given bit stream of encoded data for a given video clip, wherein each of the multiple sets comprises a rate parameter and a decoder buffer size parameter for a reference decoder model that specifies constraints on fluctuations of the given bit stream of encoded data for the given video clip, and wherein each of the multiple sets indicates a different and alternative combination of rate parameter and decoder buffer size parameter for the same video images in the given bit stream of encoded data for the given video clip; and

with the video decoder, processing the multiple sets, wherein the multiple sets are concurrently available for use in determination of an operating condition, and wherein the operating condition indicates peak rate or decoder buffer size for decoding the encoded data for the given video clip; and
with the video decoder, decoding the encoded data for the given video clip.

93. (previously presented) The method of claim 92 wherein the decoder buffer size parameter for each of the multiple sets is different.

94. (previously presented) The method of claim 92 wherein the rate parameter for each of the multiple sets is different.

95. (currently amended) The method of claim 92 further comprising, at the video decoder, receiving a number parameter that indicates how many sets of reference decoder parameters are

signaled for the given bit stream of encoded data for the given video clip.

96. (currently amended) The method of claim 92 further comprising:
at the video decoder, receiving multiple additional sets of reference decoder parameters
signaled for the given bit stream of encoded data for the given video clip; and
with the video decoder, processing the multiple additional sets, wherein the multiple additional
sets are concurrently available for use in re-determination of the operating condition.

97. (previously presented) The method of claim 92 wherein the multiple sets are signaled out
of band.

98. (previously presented) The method of claim 92 wherein the processing comprises reading
the multiple sets from a stream header of the bit stream.

99. (previously presented) The method of claim 92 wherein the processing comprises
determining the operating condition.

100. (previously presented) The method of claim 92 wherein each of the multiple sets further
comprises an initial buffer fullness parameter.

101. (previously presented) The method of claim 92 wherein each of the multiple sets
represents a different leaky bucket model for the given bit stream of encoded data for the given video
clip.

102. (previously presented) The method of claim 92 wherein each of the multiple sets
represents a different point along a rate-decoder buffer size curve for the given bit stream of encoded
data for the given video clip.

103. (previously presented) The method of claim 92 wherein the given video clip is part of a
video sequence.

104. (previously presented) The method of claim 92 wherein the peak rate corresponds to a drive speed for a disk drive during the decoding the encoded data.

105. (previously presented) The method of claim 92 wherein the peak rate corresponds to a transmission rate for a network connection during the decoding the encoded data.

106. (previously presented) The method of claim 92 wherein the decoding the encoded data occurs during live video transmission for the given video clip.

107. (previously presented) The method of claim 92 wherein the decoding the encoded data occurs during on-demand transmission for the given video clip.

108. (currently amended) A computer-implemented method of decoding video with a video decoder, the method comprising:

at the video decoder, receiving a number parameter that indicates how many sets of reference decoder parameters are signaled for a given bit stream of encoded data for a given video clip;

at the video decoder, receiving multiple sets of reference decoder parameters signaled for the given bit stream of encoded data for the given video clip, wherein each of the multiple sets comprises a rate parameter and a decoder buffer size parameter for a reference decoder model that specifies constraints on fluctuations of the given bit stream of encoded data for the given video clip, and wherein each of the multiple sets represents a different and alternative point along a rate-decoder buffer size curve for the same video images in the given bit stream of encoded data for the given video clip; ~~and~~

with the video decoder, processing the multiple sets, wherein the multiple sets are concurrently available for use in determination of an operating condition, and wherein the operating condition indicates peak rate or decoder buffer size for decoding the encoded data for the given video clip; and
with the video decoder, decoding the encoded data for the given video clip.

109. (previously presented) The method of claim 108 wherein the decoder buffer size parameter for each of the multiple sets is different, and wherein the rate parameter for each of the

multiple sets is different.

110. (previously presented) The method of claim 108 wherein the number parameter and the multiple sets are signaled out of band.

111. (previously presented) The method of claim 108 wherein the processing comprises reading the multiple sets from a stream header of the bit stream.

112. (previously presented) The method of claim 108 wherein the processing comprises determining the operating condition.

113. (previously presented) The method of claim 112 wherein the determining comprises selecting a parameter of one of the multiple received sets, interpolating between parameters of two of the multiple sets, or extrapolating from a parameter of one of the multiple sets.

114. (previously presented) The method of claim 112 wherein the peak rate corresponds to a drive speed for a disk drive during the decoding the encoded data.

115. (previously presented) The method of claim 112 wherein the peak rate corresponds to a transmission rate for a network connection during the decoding the encoded data.

116. (previously presented) The method of claim 112 wherein the decoding the encoded data occurs during on-demand transmission for the given video clip.

117. (currently amended) A computer-implemented method of decoding video with a video decoder, the method comprising:

at the video decoder, receiving multiple sets of reference decoder parameters signaled for a given bit stream of encoded data for a given video clip, wherein each of the multiple sets comprises a rate parameter and a decoder buffer size parameter for a reference decoder model that specifies constraints on fluctuations of the given bit stream of encoded data for the given video clip, and wherein

each of the multiple sets indicates a different and alternative combination of rate parameter and decoder buffer size parameter for the same video images in the given bit stream of encoded data for the given video clip;

with the video decoder, processing the multiple sets, wherein the multiple sets are concurrently available for use in determination of an operating condition, and wherein the operating condition indicates peak rate or decoder buffer size for decoding the encoded data for the given video clip;

at the video decoder, receiving multiple additional sets of reference decoder parameters signaled for the given bit stream of encoded data for the given video clip; ~~and~~

with the video decoder, processing the multiple additional sets, wherein the multiple additional sets are concurrently available for use in re-determination of the operating condition, and wherein each of the multiple sets and multiple additional sets represents a different leaky bucket model for the given video clip; and

with the video decoder, decoding the encoded data for the given video clip.

118. (previously presented) The method of claim 117 wherein the decoder buffer size parameter for each of the multiple sets is different, and wherein the rate parameter for each of the multiple sets is different.

119. (previously presented) The method of claim 117 wherein the processing comprises determining the operating condition, and wherein the determining comprises selecting a parameter of one of the multiple received sets, interpolating between parameters of two of the multiple sets, or extrapolating from a parameter of one of the multiple sets.

120. (previously presented) The method of claim 117 wherein the processing comprises determining the operating condition, and wherein the determining comprises setting the peak rate based upon one or more of the decoder buffer size parameters of the multiple sets or setting the decoder buffer size based upon one or more of the rate parameters of the multiple sets.

121. (currently amended) A computer-implemented method of decoding video with a video decoder, the method comprising:

at the video decoder, receiving a number parameter that indicates how many sets of reference decoder parameters are signaled for a given bit stream of encoded data for a given video clip;

at the video decoder, receiving multiple sets of reference decoder parameters signaled for the given bit stream of encoded data for the given video clip, wherein each of the multiple sets comprises a rate parameter and a decoder buffer size parameter for a reference decoder model that specifies constraints on fluctuations of the given bit stream of encoded data for the given video clip;

with the video decoder, determining an operating condition using any of the multiple sets, wherein the operating condition indicates peak rate or decoder buffer size for decoding the encoded data for the given video clip, wherein the multiple sets are concurrently available for use in the determining the operating condition, and wherein each of the multiple sets represents a different and alternative point along a rate-decoder buffer size curve for the same video images in the given bit stream of encoded data for the given video clip; and

~~at a decoder~~ with the video decoder, ~~receiving and~~ decoding the encoded data for the given video clip in accordance with the operating condition.

122. (previously presented) The method of claim 121 wherein the decoder buffer size parameter for each of the multiple sets is different, and wherein the rate parameter for each of the multiple sets is different.

123. (previously presented) The method of claim 121 wherein the number parameter and the multiple sets are signaled in a stream header for the given bit stream of encoded data for the given video clip.

124. (previously presented) The method of claim 121 wherein the number parameter and the multiple sets are signaled out-of-band for the given video clip.

125. (previously presented) The method of claim 121 wherein the determining comprises selecting a parameter of one of the multiple received sets, interpolating between parameters of two of the multiple sets, or extrapolating from a parameter of one of the multiple sets.

126. (previously presented) The method of claim 121 wherein the decoder is implemented in a handheld computing device, in a personal computer, or in a disk media player.

127. (previously presented) The method of claim 121 wherein the decoding the encoded data occurs during on-demand transmission for the given video clip.

128. (currently amended) A ~~system~~ video decoder comprising:

a processor; and

non-volatile storage media storing computer-executable instructions for causing the video decoder to perform a method of decoding video, the method comprising:

_____ at the video decoder, ~~one or more modules~~ for receiving multiple sets of reference decoder parameters signaled for a given bit stream of encoded data for a given video clip, wherein each of the multiple sets comprises a rate parameter and a decoder buffer size parameter for a reference decoder model that specifies constraints on fluctuations of the given bit stream of encoded data for the given video clip, and wherein each of the multiple sets indicates a different and alternative combination of rate parameter and decoder buffer size parameter for the same video images in the given bit stream of encoded data for the given video clip; and

_____ with the video decoder, one or more modules for processing the multiple sets, wherein the multiple sets are concurrently available for use in determination of an operating condition, and wherein the operating condition indicates peak rate or decoder buffer size for decoding the encoded data for the given video clip; and

_____ with the video decoder, decoding the encoded data for the given video clip.

129. (currently amended) The ~~system~~ video decoder of claim 128 wherein the decoder buffer size parameter for each of the multiple sets is different, and wherein the rate parameter for each of the multiple sets is different.

130. (currently amended) The ~~system~~ video decoder of claim 128 wherein the processing comprises determining the operating condition.

131. (currently amended) The ~~system~~ video decoder of claim 130 wherein the determining comprises selecting a parameter of one of the multiple received sets, interpolating between parameters of two of the multiple sets, or extrapolating from a parameter of one of the multiple sets.

132. (currently amended) A ~~computer-readable non-volatile storage~~ medium storing computer-executable instructions for causing a computer system programmed thereby to perform a method of decoding video with a video decoder, the method comprising:

at the video decoder, receiving multiple sets of reference decoder parameters signaled for a given bit stream of encoded data for a given video clip, wherein each of the multiple sets comprises a rate parameter and a decoder buffer size parameter for a reference decoder model that specifies constraints on fluctuations of the given bit stream of encoded data for the given video clip, and wherein each of the multiple sets indicates a different and alternative combination of rate parameter and decoder buffer size parameter for the same video images in the given bit stream of encoded data for the given video clip; ~~and~~

with the video decoder, processing the multiple sets, wherein the multiple sets are concurrently available for use in determination of an operating condition, and wherein the operating condition indicates peak rate or decoder buffer size for decoding the encoded data for the given video clip; and
with the video decoder, decoding the encoded data for the given video clip.